



12.1" Open Frame Touch Panel PC

Model:EB-1210EM



Specification:

O/S	Driver for Linux ,Windows
CPU	Intel Atom D2550, 1.86GHZ
Chipsets	Intel NM10
RAM	2GByte DDR3-1333 / 4GByte DDR3-1333
Hard Drive	16GByte / 32GByte / 64GByte / 128GByte mSATA SSD
Graphic	Intel GMA3000,640MHz
Audio	Realtek HD ALC 662
LAN	Realtek RTL8111E, 2*10/100/1000MBit RJ45 Ports
USB	8* USB 2.0 ports, 4 as external
External Ports	4*USB 2.0
	2* COM-RS232
	1*RS485/422
	2*RJ45
	VGA
	Audio-in/ Audio-out
	PS/2(Mouse Keyboard)
	LPT
	Power on/off
	DC-IN (screwable)
Internal port	2*Sata 300MB/S (1*MSATA)
	1*MiniPCI-E
	PCI
	SATA2
	4*COM
Power consumption	20W
Input Voltage	8V~36V DC-IN (Wide voltage)
Operating Temperature	,-10℃ to +60℃
Storage Temperature	,-20℃ to +70℃
Driver	Windows, Linux;
Display	245.76x184.32mm
Aspect Ratio	4:3
Physical Resolution	1024 (W)*768(H)

Brightness	420cd/m ²
Contrast Ratio	550:1
React time	2ms/6ms
Viewing Angle	80/80/60/80 (Typ.)(CR≥10) (L/R/U/D)
Touch Panel	5 wire resistive touch
Touch Panel Driver	Windows, Linux, Marc
React time touch panel	<10 ms
Surface Hardness	3H
Power Supply	AC100~240V,DC12V
Cooling System	Fanless
Front Panel	
Install	Embedded , VESA100
Case	Stainless steel and Aluminum
Size(WxHxD)	315x210.1x71.7mm

Optional	<i>W-lan optional</i>
	<i>Saw touch panel</i>
	<i>Outside HDD</i>
	<i>Luminance(600cd/ m² , 1000cd/ m² ,)</i>
	<i>12V DC-IN</i>
	<i>Advanced RAM and SSD/HDD</i>

Packing list:
1* CD Driver
1* PC User Menu
1* Power Adapter
1* Touch Pen

Dimensions

