



RESUN 12.1" Stainless Steel Touch Panel PC -RFID

Model: EB-121RA



Specification:

| | |
|--|--|
| O/S | Drivers for Windows / Linux |
| CPU | Intel Atom D2550, 1.86GHZ (optional) |
| Chipsets | North bridge: Intel NM10 |
| RAM | 1*2GByte DDR3 (optional) |
| Hard Drive | SSD 32G (optional) |
| Graphic | Intel GMA3650,640MHz |
| Audio | Realtek HD ALC 662, 2*2W Loudspeaker |
| LAN | Realtek RTL8111E, 1*10/100/1000MBit RJ45 Ports |
| USB | 6* USB 2.0 ports, 4 as external |
| RFID | RFID 125KHZ(ID Card) or 13.56MHZ(IC Card) |
| External Ports (Can be customized) | VGA |
| | HDMI |
| | 4*USB |
| | 2* RS232 |
| | 1*RJ45 |
| | EAR |
| | MIC |
| | WLAN |
| Internal port | AC-in(100-240V) built-in inside |
| | 2*Sata 300MB/S (1*MSATA) |
| | 1*MiniPCI-E |
| Power consumption(W) | 36 |
| Stand-By-Consumption (W) | ≤1 |
| Operating Temperature | ,-10℃ to +60℃ |
| Storage Temperature | ,-20℃ to +70℃ |
| Driver | Windows, Linux; |
| Display(mm) | 263x165 |
| Aspect Ratio | 16:10 |
| Physical Resolution | 1280 (W)*800(H) |
| Maximum knowable resolution | 1920 (W)*1200(H) |
| Luminance(cd/m ²) | 300 |
| Contrast Ratio | 600:1 |
| React time | 2ms/6ms |
| Visual angle h:v(°) | 160;160 |
| Touch Panel | 4 wire resistive touch |

| | |
|------------------------|---|
| Touch Panel Driver | Windows, Linux, |
| React time touch panel | <10 ms |
| Surface Hardness | 3H |
| Input Force(g) | 20-150 |
| Knock Test | 30,000,000 times |
| Cooling System | Fanless |
| Protection grade | The front panel IP55 |
| Install | Panel,Wall,Rack,Stand,Arm VESA100 |
| Case | Stainless steel |
| Size(WxHxD)(mm) | 385x227x100 |
| Optional | CPU:N2600/2807/J1900 |
| | 2*LAN(RJ45) |
| | Network 3G/4G |
| | W-lan optional |
| | 5 wire resistive touch |
| | Scanner |
| | other sizes in the display.(7~19 inch) |

Packing list:

- 1* CD Driver
- 1* PC User Menu
- 1* Power Adapter
- 1* Touch Pen

Dimensions

